

DUST & STATIC

4125 IONISED AIRGUN

The 4125 is our most powerful airgun for neutralising static electricity and removing dust and other contaminants.

It is available in two variants for top or bottom air feed.

- > The 4125 is suitable for the most demanding cleaning and static neutralising work.
- > The open construction of the ionisation head and the airflow amplifier nozzle give the 4125 operational efficiency, producing maximum ionisation with maximum airflow.
- > The hand trigger, in addition to being robust and ergonomic, gives the operator excellent control of the airflow.
- > The air consumption is minimised by the air nozzle which amplifies the compressed air by 20:1.
- > Ergonomic full-hand trigger is suitable for all day use, unlike designs using one or two fingers.
- > It is robust and modularly designed for easy repair and maintenance.



Specification

Construction:	Stainless steel ionisation head and guard, PTFE ionising head, plastic handle, aluminium nozzle.
Operation:	Maximum air pressure 10 Bar. Typical working pressure is 5 Bar. Air consumption at 5 Bar is 560 lit/min for continuous operation.
Cable:	Purpose designed Hi-Flex HT cable is flexible, light and very durable. Available in lengths of 3 m, 5 m, 7 m and 10 m.
Safety:	The ionisation system is shockless and meets OSHA and other Safety Standards. The nozzle cannot be dead-ended.
Noise	At 5 Bar noise level is 74 dBA, measured at 1 m.
Power Unit:	Use with Fraser 5.5 kv or 6 kV Power Units - see separate Datasheets
Thrust (airspeed x volume which represents cleaning power)	At 5 Bar the thrust at a distance of 100 mm is a market leading 5.2 N.
Air Connections & Pipe	1/4 BSP threaded connection. Supply pipe should be at least 6 mm internal diameter for full performance. If the pipe is long then a bigger bore may be needed to prevent pressure drop. Air fitting supplied (unless otherwise ordered) is for 8 mm OD push in pipe.

How it works

The Ionised Airgun consists of a hand trigger, air nozzle and an ionisation head engineered into the finger guard.

When the trigger is pulled air travels at high speed from the nozzle picking up the ionised air produced by the ionisation head.

The ionised air is blown at high speed towards the object. The ionisation kills the static electricity, allowing the dust to be blown off.

Both the object and the dust will be static-free so preventing re-attraction.

The 4125 requires clean and dry compressed air.

Applications:

The 4125 is used to clean mouldings, plastic sheets, automobiles, electrical assemblies, displays, even helicopters and jetfighter cockpits - wherever dust and static are a problem.

Manufactured without compromising performance and long life.

- **Maximum ionisation.**
The ions are produced outside of the gun resulting in a performance which is many times more effective than traditional internal ionisation heads.
- **Ergonomic.**
Four finger trigger minimises fatigue and repetitive strains.
- **Air Control.**
Design of trigger/valve gives operator control over airflow.
- **Economical air consumption.**
The amplifier nozzle magnifies compressed air by up to 20:1.
- **Hi-Flex cable.**
Designed for robot use as well as ordinary hand operation.
- **Robust construction.**
Stainless steel ionisation tube. All major parts are replaceable.
- **High Thrust.**
For effective cleaning.



4125-T with top air inlet



4125-B with bottom air inlet

DUST AND STATIC

Ionised Airgun: Model 4125B/4125T

Cable Length	Product Code	Product Code
3m	E4125T-3m	E4125B-3m
5m	E4125T-5m	E4125B-5m
7m	E4125T-7m	E4125B-7m
10m	E4125T-10m	E4125B-10m

Spares and Repairs

Code	Description
80993	Nozzle
412501	Handle 4125T
412502	Handle 4125B
RECABLE	Re-cable (3m)



HP Connector

For use with HP50-1, HP50-2,
HP50- 4 & HP80 Power Units.

Model 4125B



Model 4125T



Important Ordering Information

Suitable for use with 9055-2 or HP50 Power Units, please specify which power unit the product will be used with. Please ensure all orders specify the correct information:

A Model Number

B Connection

For example:

A	B
E4125B-3m	HP
Model E4125B-3m with HP connection	