

DUST & STATIC

4825 24 V DC IONISED AIRGUN

The 4825 - a powerful and highly directional airgun for neutralising static electricity and removing dust and other contaminants.

High performance from an integrated 7 kV power supply that requires only a low voltage 24 V DC input.

- > The 4825 is suitable for the most demanding cleaning and static-neutralising work.
- > Shockless, resistively coupled tungsten emitters for unlimited life.
- > Ion balance suitable for most industrial applications.
- > Pulsed DC high voltage provides excellent charge decay performance even at longer distances.
- > Integrated high-voltage electronics means no high-voltage cables are required.
- > Protected against under-voltage, overload and reverse polarity.
- > The air consumption is minimised by the air nozzle which amplifies the compressed air by 20:1.
- > Ergonomic full-hand trigger is suitable for all day use unlike designs for one or two fingers. Gives the operator excellent control of the airflow.
- > An integrated bi-colour LED gives immediate status indication to the operator.
- > Robust construction and modular design mean the 4825 can easily be maintained or repaired.



Specification

| | |
|-----------------------------------|---|
| Construction: | Ioniser: PVC body, epoxy resin encapsulant, long-life tungsten emitters. Airgun: Plastic handle and trigger, aluminium nozzle. |
| Operation: | Maximum air pressure 10 Bar. Typical working pressure is 5 Bar. Air consumption at 5 Bar is 560 L/min for continuous operation. |
| Power Supply: | Universal 100 - 250 V AC, 24 V DC output. IEC 320 connector. Separate earth wire supplied. Fitted with 10 m of cable between the PSU and the 4825 ionised airgun. |
| High Voltage: | +/- 7 kV supply integrated inside the ioniser. |
| Safety: | The ionisation system is shockless and meets OSHA and other safety standards. |
| Protection Classification: | IP67. |
| Environment: | 0 to 55° C, 70 % RH non-condensing. |
| Noise: | At 5 Bar the noise level is 74 dBA, measured at 1 m. |
| Thrust: | At 5 Bar the thrust at a distance of 100 mm is a market leading 5.2 N. |
| Air Connections and Pipe: | ¼ BSP threaded connection. Supply pipe should be at least 6 mm internal diameter for full performance. If the pipe is long, then a larger bore may be needed to prevent pressure drop. Air fitting supplied (unless otherwise ordered) is for 8 mm OD push-in pipe. |

How it works

The 4825 Ionised Airgun consists of a hand trigger, air nozzle and a DC ionisation head mounted above the air nozzle.

When the trigger is pulled, air travels at high speed from the nozzle picking up the ionised air produced by the ionisation head.

The ionised air is blown at high speed towards the object. The ionisation kills the static electricity, allowing the dust to be blown off.

Both the object and the dust will be static-free so preventing re-attraction.

The 4825 requires clean and dry compressed air.

Applications

The 4825 Ionised Airgun is used to clean mouldings, plastic sheets, automobiles, electrical assemblies, displays, even helicopters and jetfighter cockpits - wherever dust and static are a problem.

Manufactured without compromising performance or long-life

Maximum Ionisation

The ions are produced outside of the gun resulting in a performance that is many times more effective than traditional internal ionisation heads.

Economical Air Consumption

The amplifier nozzle magnifies compressed air by up to 20:1.

24 V DC Power Supply

Removes the need for long HV cables.

Robust Construction and Modular Design

Easily maintained and all major parts can be replaced.

Ergonomic

Four-finger trigger minimises fatigue and repetitive strains.

Air Control

The design of the trigger/valve gives the operator complete control over the airflow.

High Thrust

For effective cleaning.

Accessories and Spares

| Description | Part No. | Description | Part No. |
|-----------------------------|----------|-------------|----------|
| Fraser Ioniser Cleaning Kit | 81220 | | |